


Section 1: Identification of the substance or mixture and of the supplier

Product Name: No. 2 Biodiesel Blend
 SDS Number: 778689
 Synonyms/Other Means of Identification: No. 2 B2
 No. 2 B5
 No. 2 B20
 No. 2 Biodiesel Blend - Dyed (B2, B5, B15, B20)
 No. 2 Biodiesel Blend - Winter (B2, B5, B15, B20)
 MARPOL Annex I Category: Gas Oils, Including Ship's Bunkers
 Intended Use: Fuel
 Manufacturer: ConocoPhillips
 600 N. Dairy Ashford
 Houston, Texas 77079-1175
 Emergency Health and Safety Number: Chemtrec: 800-424-9300 (24 Hours)
 Customer Service: 800-527-5476
 Technical Information: 800-527-5476
 SDS Information: Phone: 800-762-0942
 Email: MSDS@conocophillips.com
 URL: www.conocophillips.com

Section 2: Hazard(s) Identification

DANGER

Flammable liquid and vapor. (H226)*
 Causes skin irritation. (H315)*
 Harmful if inhaled. (H332)*
 May be fatal if swallowed and enters airways. (H304)*
 May cause damage to organs through prolonged or repeated exposure. (H373)*
 Suspected of causing cancer. (H351)*
 Toxic to aquatic life with long lasting effects. (H411)*



Precautionary Statement(s):

Obtain special instructions before use. (P201)*
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. (P210)*
 Do not breathe vapors or mists. (P260)*
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. (P301+P310)*
 Do NOT induce vomiting. (P331)*
 Dispose of contents/container to approved disposal facility. (P501)*

* (Applicable GHS hazard code.)

Section 3: Composition / Information on Ingredients

Component	CASRN	Concentration ¹
Diesel Fuel No. 2	68476-34-6	80-98.5

Section 3: Composition / Information on Ingredients

B100 Biodiesel	67784-80-9	1.5-20
Naphthalene	91-20-3	<1

Total Sulfur: < 0.1 wt%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Section 4: First Aid Measures

Eye Contact: If irritation or redness develops from exposure, flush eyes with clean water. If symptoms persist, seek medical attention.

Skin Contact: Remove contaminated shoes and clothing, and flush affected area(s) with large amounts of water. If skin surface is damaged, apply a clean dressing and seek medical attention. If skin surface is not damaged, cleanse affected area(s) thoroughly by washing with mild soap and water or a waterless hand cleaner. If irritation or redness develops, seek medical attention. Wash contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician. (see Note to Physician)

Inhalation (Breathing): If respiratory symptoms or other symptoms of exposure develop, move victim away from source of exposure and into fresh air in a position comfortable for breathing. If symptoms persist, seek immediate medical attention. If victim is not breathing, clear airway and immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

Ingestion (Swallowing): Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. If victim is drowsy or unconscious and vomiting, place on the left side with the head down. If possible, do not leave victim unattended and observe closely for adequacy of breathing. Seek medical attention.

Notes to Physician: When using high-pressure equipment, injection of product under the skin can occur. In this case, the casualty should be sent immediately to hospital. Do not wait for symptoms to develop. High-pressure hydrocarbon injection injuries may produce substantial necrosis of underlying tissue despite an innocuous appearing external wound. These injuries often require extensive emergency surgical debridement and all injuries should be evaluated by a specialist in order to assess the extent of injury. Early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

Medical Conditions Aggravated by Exposure: Conditions which may be aggravated by exposure include skin disorders, blood disorders, liver disorders and immune system disorders.

Section 5: Fire-Fighting Measures

NFPA 704 Hazard Class

Health: 1 Flammability: 2 Instability: 0 (0-Minimal, 1-Slight, 2-Moderate, 3-Serious, 4-Severe)

Unusual Fire & Explosion Hazards: Flammable. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe). Vapors may travel considerable distances to a source of ignition where they can ignite, flash back, or explode. May create vapor/air explosion hazard indoors, in confined spaces, outdoors, or in sewers. This product will float and can be reignited on surface water. Vapors are heavier than air and can accumulate in low areas. If container is not properly cooled, it can rupture in the heat of a fire.

Extinguishing Media: Dry chemical, carbon dioxide, or foam is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Water may be ineffective for extinguishment, unless used under favorable conditions by experienced fire fighters.

Fire Fighting Instructions: For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When the potential chemical hazard is unknown, in enclosed or confined spaces, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8).

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done safely. Avoid spreading burning liquid with water used for cooling purposes.

Hazardous Combustion Products: Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of nitrogen and sulfur may also be formed.

See Section 9 for Flammable Properties including Flash Point and Flammable (Explosive) Limits

Section 6: Accidental Release Measures

Personal Precautions: Flammable. Spillages of liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition and hot metal surfaces away from spill/release if safe to do so. The use of explosion-proof electrical equipment is recommended. Stay upwind and away from spill/release. Avoid direct contact with material. For large spillages, notify persons down wind of the spill/release, isolate immediate hazard area and keep unauthorized personnel out. Wear appropriate protective equipment, including respiratory protection, as conditions warrant (see Section 8). See Sections 2 and 7 for additional information on hazards and precautionary measures.

Environmental Precautions: Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems, and natural waterways. Use foam on spills to minimize vapors. Use water sparingly to minimize environmental contamination and reduce disposal requirements. If spill occurs on water notify appropriate authorities and advise shipping of any hazard. Spills into or upon navigable waters, the contiguous zone, or adjoining shorelines that cause a sheen or discoloration on the surface of the water, may require notification of the National Response Center (phone number 800-424-8802).

Methods for Containment and Clean-Up: Notify relevant authorities in accordance with all applicable regulations. Immediate cleanup of any spill is recommended. Dike far ahead of spill for later recovery or disposal. Absorb spill with inert material such as sand or vermiculite, and place in suitable container for disposal. If spilled on water remove with appropriate methods (e.g. skimming, booms or absorbents). In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.

Recommended measures are based on the most likely spillage scenarios for this material; however local conditions and regulations may influence or limit the choice of appropriate actions to be taken.

Section 7: Handling and Storage

Precautions for safe handling: Keep away from ignition sources such as heat/sparks/open flame – No smoking. Take precautionary measures against static discharge. Nonsparking tools should be used. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors or mists. Use only outdoors or in well-ventilated area. Wear protective gloves/clothing and eye/face protection. Wash thoroughly after handling. Use good personal hygiene practices and wear appropriate personal protective equipment (see section 8).

Flammable. May vaporize easily at ambient temperatures. The vapor is heavier than air and may create an explosive mixture of vapor and air. Beware of accumulation in confined spaces and low lying areas. Open container slowly to relieve any pressure. Electrostatic charge may accumulate and create a hazardous condition when handling or processing this material. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. The use of explosion-proof electrical equipment is recommended and may be required (see appropriate fire codes). Refer to NFPA-70 and/or API RP 2003 for specific bonding/grounding requirements. Do not enter confined spaces such as tanks or pits without following proper entry procedures such as ASTM D-4276 and 29CFR 1910.146. Do not wear contaminated clothing or shoes. Keep contaminated clothing away from sources of ignition such as sparks or open flames.

High pressure injection of hydrocarbon fuels, hydraulic oils or greases under the skin may have serious consequences even though no symptoms or injury may be apparent. This can happen accidentally when using high pressure equipment such as high pressure grease guns, fuel injection apparatus or from pinhole leaks in tubing of high pressure hydraulic oil equipment.

For use as a motor fuel only. Do not use as a solvent due to its flammable and potentially toxic properties. Siphoning by mouth can result in lung aspiration which can be harmful or fatal.

The use of hydrocarbon fuel in an area without adequate ventilation may result in hazardous levels of incomplete combustion products (e.g. carbon monoxide, oxides of sulfur and nitrogen, benzene and other hydrocarbons) and/or dangerously low oxygen levels.

Diesel engine exhaust contains hazardous combustion products and has been classified as a probable cancer hazard in humans.

Static Accumulation Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding of tanks, transfer piping, and storage tank level floats are necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. Special care should be given to ensure that special slow load procedures for "switch loading" are followed to avoid the static ignition hazard that can exist when higher flash point material (such as fuel oil or diesel) is loaded into tanks previously containing low flash point products (such as gasoline or naphtha). For more information, refer to OSHA Standard 29 CFR 1910.106, 'Flammable and Combustible Liquids', National Fire Protection Association (NFPA 77, 'Recommended Practice on Static Electricity', and/or the American Petroleum Institute (API) Recommended Practice 2003, 'Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents'.

Conditions for safe storage: Keep container(s) tightly closed and properly labeled. Use and store this material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Store only in approved containers. Post area "No Smoking or Open Flame." Keep away from any incompatible material (see Section 10). Protect container(s) against physical damage. Outdoor or detached storage is preferred. Indoor storage should meet OSHA standards and appropriate fire codes.

"Empty" containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death. "Empty" drums should be completely drained, properly bunged, and promptly shipped to the supplier or a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Before working on or in tanks which contain or have contained this material, refer to OSHA regulations, ANSI Z49.1, and other references pertaining to cleaning, repairing, welding, or other contemplated operations.

Section 8: Exposure Controls / Personal Protection

Component	ACGIH	OSHA	Other
Diesel Fuel No. 2	TWA: 100 mg/m ³	---	---
Naphthalene	STEL: 15 ppm	TWA: 10 ppm TWA: 50 mg/m ³	TWA: 0.2 mg/m ³ (as total of 17 PNA's measured by NIOSH Method 5506) (ConocoPhillips Guidelines)

Note: State, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or your local agencies, for further information.

Engineering controls: If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional engineering controls may be required.

Eye/Face Protection: The use of eye protection that meets or exceeds ANSI Z.87.1 is recommended to protect against potential eye contact, irritation, or injury. Depending on conditions of use, a face shield may be necessary.

Skin/Hand Protection: The use of gloves impervious to the specific material handled is advised to prevent skin contact. Users should check with manufacturers to confirm the breakthrough performance of their products. Depending on exposure and use conditions, additional protection may be necessary to prevent skin contact including use of items such as chemical resistant boots, aprons, arm covers, hoods, coveralls, or encapsulated suits. Suggested protective materials: Nitrile

Respiratory Protection: Where there is potential for airborne exposure above the exposure limit a NIOSH certified air purifying respirator equipped with organic vapor cartridges/canisters may be used.

A respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed whenever workplace conditions warrant a respirator's use. Air purifying respirators provide limited protection and cannot be used in atmospheres that exceed the maximum use concentration (as directed by regulation or the manufacturer's instructions), in oxygen deficient (less than 19.5 percent oxygen) situations, or under conditions that are immediately dangerous to life and health (IDLH).

Other Protective Equipment: Eye wash and quick-drench shower facilities should be available in the work area. Thoroughly clean shoes and wash contaminated clothing before reuse.

Suggestions provided in this section for exposure control and specific types of protective equipment are based on readily available information. Users should consult with the specific manufacturer to confirm the performance of their protective equipment. Specific situations may require consultation with industrial hygiene, safety, or engineering professionals.

Section 9: Physical and Chemical Properties

Note: Unless otherwise stated, values are determined at 20°C (68°F) and 760 mm Hg (1 atm). Data represent typical values and are not intended to be specifications.

Appearance:	Straw colored to dyed red
Physical Form:	Liquid
Odor:	Diesel fuel
Odor Threshold:	No data
pH:	Not applicable
Vapor Pressure:	<1 mm Hg
Vapor Density (air=1):	>1
Initial Boiling Point/Range:	300-690 °F / 149-366 °C
Melting/Freezing Point:	No data

Solubility in Water:	Negligible
Partition Coefficient (n-octanol/water) (Kow):	No data
Specific Gravity (water=1):	0.81-0.88 @ 60°F (15.6°C)
Bulk Density:	6.9 - 7.4 lbs/gal
Viscosity:	1.9 - 4.1 cSt @ 40°C
Percent Volatile:	Negligible
Evaporation Rate (nBuAc=1):	No data
Flash Point:	125 - 180°F / 52 - 82°C
Test Method:	Pensky-Martens Closed Cup (PMCC), ASTM D93, EPA 1010
Lower Explosive Limits (vol % in air):	0.3
Upper Explosive Limits (vol % in air):	10.0
Auto-ignition Temperature:	1131°F / 611°C

Section 10: Stability and Reactivity

Stability: Stable under normal ambient and anticipated conditions of use.

Conditions to Avoid: Avoid high temperatures and all sources of ignition. Prevent vapor accumulation.

Materials to Avoid (Incompatible Materials): Avoid contact with strong oxidizing agents and strong reducing agents.

Hazardous Decomposition Products: Not anticipated under normal conditions of use.

Hazardous Polymerization: Not known to occur.

Section 11: Toxicological Information

Information on Toxicological Effects of Substance/Mixture

Acute Toxicity	Hazard	Additional Information	LC50/LD50 Data
Inhalation	Harmful if inhaled		> 4.65 mg/L (mist)
Skin Absorption	Unlikely to be harmful		> 4.1 g/kg
Ingestion (Swallowing)	Unlikely to be harmful		> 5 g/kg

Aspiration Hazard: May be fatal if swallowed and enters airways.

Skin Corrosion/Irritation: Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

Serious Eye Damage/Irritation: Causes mild eye irritation.

Signs and Symptoms: While significant vapor concentrations are not likely, high concentrations can cause minor respiratory irritation, headache, drowsiness, dizziness, loss of coordination, disorientation and fatigue. Ingestion can cause irritation of the digestive tract, nausea, diarrhea, and vomiting.

Skin Sensitization: Not expected to be a skin sensitizer.

Respiratory Sensitization: Not expected to be a respiratory sensitizer.

Specific Target Organ Toxicity (Single Exposure): Not expected to cause organ effects from single exposure.

Specific Target Organ Toxicity (Repeated Exposure): May cause damage to organs through prolonged or repeated exposure. Dermal application of a distillate fuel component at doses > 125 mg/kg, 5 d/wk, for 13 weeks resulted in decreased liver, thymus, and spleen weights, and altered bone marrow function. Microscopic alterations included liver hypertrophy and necrosis, decreased hematopoiesis and lymphocyte depletion.

Carcinogenicity: Suspected of causing cancer. Petroleum middle distillates have been shown to cause skin tumors in mice following repeated and prolonged skin contact. Follow-up studies have shown that these tumors are produced through a non-genotoxic mechanism associated with frequent cell damage and repair, and that they are not likely to cause tumors in the absence of prolonged skin irritation.

Germ Cell Mutagenicity: No information available.

Reproductive Toxicity: No information available.

Information on Toxicological Effects of Components

Naphthalene

Carcinogenicity: Naphthalene has been evaluated in two year inhalation studies in both rats and mice. The US National Toxicology Program (NTP) concluded that there is clear evidence of carcinogenicity in male and female rats based on increased incidences of respiratory epithelial adenomas and olfactory epithelial neuroblastomas of the nose. NTP found some evidence of carcinogenicity in female mice (alveolar adenomas) and no evidence of carcinogenicity in male mice. Naphthalene has been identified as a carcinogen by IARC and NTP.

Section 12: Ecological Information

Toxicity: Experimental studies of gas oils show that acute aquatic toxicity values are typically in the range 2-20 mg/L. These values are consistent with the predicted aquatic toxicity of these substances based on their hydrocarbon compositions. They should be regarded as toxic to aquatic organisms, with the potential to cause long term adverse effects in the aquatic environment. Classification: H411; Chronic Cat 2.

Persistence and Degradability: Gas oils are complex combinations of individual hydrocarbon species. Based on the known or expected properties of individual constituents, category members are not predicted to be readily biodegradable. Some hydrocarbon constituents of gas oils are predicted to meet the criteria for persistence; on the other hand, some components can be easily degraded by microorganisms under aerobic conditions.

Persistence per IOPC Fund definition: Non-Persistent

Bioaccumulative Potential: Gas oil components have measured or calculated Log Kow values in the range of 3.9 to 6 which indicates a high potential to bioaccumulate. Lower molecular weight compounds are readily metabolized and the actual bioaccumulation potential of higher molecular weight compounds is limited by the low water solubility and large molecular size.

Mobility in Soil: Releases to water will result in a hydrocarbon film floating and spreading on the surface. For the lighter components, volatilization is an important loss process and reduces the hazard to aquatic organisms. In air, the hydrocarbon vapors react readily with hydroxyl radicals with half-lives of less than one day. Photooxidation on the water surface is also a significant loss process particularly for polycyclic aromatic compounds. In water, the majority of components will be adsorbed on sediment. Adsorption is the most predominant physical process on release to soil. Adsorbed hydrocarbons will slowly degrade in both water and soil.

Other Adverse Effects: None anticipated.

Section 13: Disposal Considerations

The generator of a waste is always responsible for making proper hazardous waste determinations and needs to consider state and local requirements in addition to federal regulations.

This material, if discarded as produced, would not be a federally regulated RCRA "listed" hazardous waste. However, it would likely be identified as a federally regulated RCRA hazardous waste for the following characteristic(s) shown below. See Sections 7 and 8 for information on handling, storage and personal protection and Section 9 for physical/chemical properties. It is possible that the material as produced contains constituents which are not required to be listed in the MSDS but could affect the hazardous waste determination. Additionally, use which results in chemical or physical change of this material could subject it to regulation as a hazardous waste.

Container contents should be completely used and containers should be emptied prior to discard. Container residues and rinseates could be considered to be hazardous wastes.

EPA Waste Number(s)

- D001 - Ignitability characteristic

Section 14: Transport Information

U.S. Department of Transportation (DOT)

Shipping Description:	<i>Aquatic toxicity studies indicate material may be classified as a Marine Pollutant. This classification impacts bulk and water shipments.</i> NA1993, Diesel fuel, Combustible liquid, III
Non-Bulk Package Marking:	Not Regulated [49 CFR 173.150(f)(2)]
Non-Bulk Package Labeling:	Not Regulated [49 CFR 173.150(f)(2)]
Bulk Package/Placard Marking:	Combustible / 1993
Packaging - References:	None; None; 49 CFR 173.241 (Exceptions; Non-bulk; Bulk)
Emergency Response Guide:	128

Section 14: Transport Information

Note: *May also be shipped as: Diesel fuel, Combustible liquid, UN1202, III Bulk Package/Placard Marking would also be changed to: 1202 Container(s) greater than 5 liters (liquids) or 5 kilograms (solids), shipped by water mode and ALL bulk shipments may require the shipping description to contain the "Marine Pollutant" notation [49 CFR 172.203(l)] and the container(s) to display the [Marine Pollutant Mark] [49 CFR 172.322]. The following alternate shipping description order may be used until January 1, 2013: Proper Shipping name, Hazard Class or Division, (Subsidiary Hazard If any), UN or NA number, Packing Group Other shipping description elements may be required for DOT compliance.*

International Maritime Dangerous Goods (IMDG)

Shipping Description: *If flashpoint is >60° C closed-cup and the material meets the IMDG definition of a Marine Pollutant, an alternate shipping name such as "Environmentally hazardous substance, n.o.s." with hazard class 9 and PG III must be used. UN1202, Diesel fuel, 3, III, (FP° C cc), [where FP is the material's flash point in degrees Celsius closed cup]*

Non-Bulk Package Marking: Diesel fuel, UN1202

Labels: Flammable liquid

Placards/Marking (Bulk): Flammable / 1202

Packaging - Non-Bulk: P001, LP01

EMS: F-E, S-E

Note: *Proper Shipping name can be: Gas Oil or Diesel fuel or Heating Oil, light If transported in bulk by marine vessel in international waters, product is being carried under the scope of MARPOL Annex I. If container(s) is greater than 5 liters (liquids) or 5 kilograms (solids), shipment may require the shipping description to contain the "Marine Pollutant" description [IMDG 5.4.1.4.3.5] and the container(s) to display the Marine Pollutant mark [IMDG 5.2.1.6].*

International Civil Aviation Org. / International Air Transport Assoc. (ICAO/IATA)

UN/ID #: *Not regulated if flashpoint is >60° C closed-cup*
 UN1202

Proper Shipping Name: Diesel fuel

Hazard Class/Division: 3

Packing Group: III

Non-Bulk Package Marking: Diesel fuel, UN1202

Labels: Flammable liquid

ERG Code: 3L

Note: *If container(s) is greater than 5 liters (liquids) or 5 kilograms (solids), shipment may require the container to display the "Environmentally hazardous substance" mark [IATA 7.1.6.3].*

	LTD. QTY	Passenger Aircraft	Cargo Aircraft Only
Packaging Instruction #:	Y344	355	366
Max. Net Qty. Per Package:	10 L	60 L	220 L

Section 15: Regulatory Information

CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs (in pounds):
 This material does not contain any chemicals subject to the reporting requirements of SARA 302 and 40 CFR 372.

CERCLA/SARA - Section 311/312 (Title III Hazard Categories)

Acute Health:	Yes
Chronic Health:	Yes
Fire Hazard:	Yes
Pressure Hazard:	No
Reactive Hazard:	No

CERCLA/SARA - Section 313 and 40 CFR 372:
 This material contains the following chemicals subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR 372:

Component	Concentration ¹	de minimis
Naphthalene	<1	0.1%

EPA (CERCLA) Reportable Quantity (in pounds):

EPA's Petroleum Exclusion applies to this material - (CERCLA 101(14)).

California Proposition 65:

Warning: This material may contain detectable quantities of the following chemicals, known to the State of California to cause cancer, birth defects or other reproductive harm, and which may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):

Component	Type of Toxicity
Naphthalene	Cancer

International Hazard Classification

GHS Classification:

- H226 -- Flammable liquids -- Category 3
- H315 -- Skin corrosion/irritation -- Category 2
- H304 -- Aspiration Hazard -- Category 1
- H332 -- Acute toxicity, Inhalation -- Category 4
- H373 -- Specific target organ toxicity (repeated exposure) -- Category 2
- H351 -- Carcinogenicity -- Category 2
- H411 -- Hazardous to the aquatic environment, chronic toxicity -- Category 2

Canada:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the Regulations.

WHMIS Hazard Class

- B3 - Combustible Liquids
- D1B
- D2A
- D2B

National Chemical Inventories:

All components are either listed on the US TSCA Inventory, or are not regulated under TSCA.

All components are either on the DSL, or are exempt from DSL listing requirements.

U.S. Export Control Classification Number: EAR99

Section 16: Other Information

Date of Issue: 13-Jun-2011
Status: FINAL
Previous Issue Date: 20-Jul-2010
Revised Sections or Basis for Revision: Handling and Storage information (Section 7)
SDS Number: 778689

Guide to Abbreviations:

ACGIH = American Conference of Governmental Industrial Hygienists; CASRN = Chemical Abstracts Service Registry Number; CEILING = Ceiling Limit (15 minutes); CERCLA = The Comprehensive Environmental Response, Compensation, and Liability Act; EPA = Environmental Protection Agency; GHS = Globally Harmonized System; IARC = International Agency for Research on Cancer; IOPC = International Oil Pollution Compensation; LEL = Lower Explosive Limit; NE = Not Established; NFPA = National Fire Protection Association; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; PEL = Permissible Exposure Limit (OSHA); SARA = Superfund Amendments and Reauthorization Act; STEL = Short Term Exposure Limit (15 minutes); TLV = Threshold Limit Value (ACGIH); TWA = Time Weighted Average (8 hours); UEL = Upper Explosive Limit; WHMIS = Worker Hazardous Materials Information System (Canada)

Disclaimer of Expressed and Implied Warranties:

The information presented in this Material Safety Data Sheet is based on data believed to be accurate as of the date this Material Safety Data Sheet was prepared. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license.

This page intentionally left blank.